

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : BILACRYL® PU D611  
Revision date : 02.10.2025  
Print date : 06.10.2025

Version (Revision) : 4.0.0 (3.0.0)

## 1. Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

BILACRYL® PU D611  
Unique Formula Identifier : E410-COPR-S003-GKHY

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Coatings and paints, fillers, putties, thinners. The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier :** MONOPOL AG  
**Street/P.O.Box :** Oberrohrdorferstrasse 51  
**Country code/Postal code/Town/City :** 5442 Fislisbach  
**Telephone :** +41 56 484 77 77  
**Telefax :** +41 56 484 77 99  
**Contact :** info@monopol-colors.ch

### 1.4 Emergency telephone number

+41 44 251 51 51

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P273 Avoid release to the environment.  
P501 Dispose of contents/container to hazardous waste

##### Special rules for supplemental label elements for certain mixtures

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE ; REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

#### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 3. Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

3-BUTOXYPROPAN-2-OL ; REACH No. : None ; EC No. : 225-878-4; CAS No. : 5131-66-8  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** BILACRYL® PU D611  
**Revision date :** 02.10.2025  
**Print date :** 06.10.2025

**Version (Revision) :** 4.0.0 (3.0.0)

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Carc. 2 ; H351 (Inhalation)

Hydrocarbons, C9, aromatics ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 128601-23-0

Weight fraction :  $\geq 1 - < 2.5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6

Weight fraction :  $\geq 1 - < 2.5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

1-METHOXY-2-PROPANOL ; REACH No. : 01-2119457435-35 ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

2-DIMETHYLAMINOETHANOL ; EC No. : 203-542-8; CAS No. : 108-01-0

Weight fraction :  $< 0.5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 3 ; H331 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 STOT SE 3 ; H335

Specific Conc. Limits : STOT SE 3 ; H335: C  $\geq 5 \%$

BRONOPOL (INN) ; EC No. : 200-143-0; CAS No. : 52-51-7

Weight fraction :  $< 0.025 \%$   
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 Aquatic Acute 1 ; H400 Aquatic Chronic 2 ; H411

Specific Conc. Limits : (M Acute=10)

3-IODO-2-PROPYNYL BUTYLCARBAMATE ; EC No. : 259-627-5; CAS No. : 55406-53-6

Weight fraction :  $< 0.025 \%$   
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H331 STOT RE 1 ; H372 (larynx) Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Specific Conc. Limits : (M Chronic=1) • (M Acute=10)

1,2-BENZISOTHIAZOL-3(2H)-ONE ; REACH No. : Pre-Registration ; EC No. : 220-120-9; CAS No. : 2634-33-5

Weight fraction :  $\geq 0.005 - < 0.05 \%$   
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9

Weight fraction :  $\geq 0.00015 - < 0.0015 \%$   
Classification 1272/2008 [CLP] : Acute Tox. 2 ; H310 Acute Tox. 2 ; H330 Acute Tox. 3 ; H301 Skin Corr. 1C ; H314 Eye Dam. 1 ; H318 Skin Sens. 1A ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 EUH071

Specific Conc. Limits : Eye Dam. 1 ; H318: C  $\geq 0.6 \%$  • Skin Corr. 1C ; H314: C  $\geq 0.6 \%$  • Eye Irrit. 2 ; H319: C  $\geq 0.06 \%$  • Skin Irrit. 2 ; H315: C  $\geq 0.06 \%$  • Skin Sens. 1A ; H317: C  $\geq 0.0015 \%$  • (M=100)

### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### 3.3 Additional information

paint material, waterborne

## 4. First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : BILACRYL® PU D611  
Revision date : 02.10.2025  
Print date : 06.10.2025

Version (Revision) : 4.0.0 (3.0.0)

## Following inhalation

Remove casualty to fresh air and keep warm and at rest. Keep at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice.

## In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

## After eye contact

Remove contact lenses, keep eyelids open. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

## Following ingestion

Call a physician in any case! Keep at rest. Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

None

## 5. Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO2) Water spray jet

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

Use suitable breathing apparatus.

### 5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. See protective measures under point 7 and 8.

### 6.2 Environmental precautions

Cover drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean with detergents. Avoid solvent cleaners.

### 6.4 Reference to other sections

None

## 7. Handling and storage

### 7.1 Precautions for safe handling

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** BILACRYL® PU D611  
**Revision date :** 02.10.2025  
**Print date :** 06.10.2025

**Version (Revision) :** 4.0.0 (3.0.0)

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharges. Wear anti-static footwear and clothing. It is recommended to design all work processes always so that the following is excluded: Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Comply with the health and safety at work laws. For personal protection see Section 8. Respiratory protection necessary at: spray application

### Protective measures

#### Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Always close containers tightly after the removal of product. Never use pressure to empty container. Only allow access to authorised staff. Keep away from sources of ignition - No smoking. Always close containers tightly after the removal of product. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

**Storage class (TRGS 510) ( D ) :** 12

#### Do not store together with

Do not store together with Acid alkali Oxidizing agent

#### Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from sources of ignition - No smoking. Keep in a cool, well-ventilated place. Keep in a cool, well-ventilated place. Comply with the health and safety at work laws.

### 7.3 Specific end use(s)

None

## 8. Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

BARIUM SULPHATE ; CAS No. : 7727-43-7

Limit value type (country of origin) : MAK ( CH )

Parameter : A: respirable fraction

Limit value : 3 mg/m<sup>3</sup>

Version : 22.02.2021

TITANIUM DIOXIDE ; CAS No. : 13463-67-7

Limit value type (country of origin) : MAK ( CH )

Parameter : A: respirable fraction

Limit value : 3 mg/m<sup>3</sup>

Remark : SSC

Version : 22.02.2021

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : MAK ( CH )

Limit value : 360 mg/m<sup>3</sup> / 100 ml/m<sup>3</sup>

Remark : SSC B

Version : 22.02.2021

Limit value type (country of origin) : STEL ( CH )

Limit value : 720 mg/m<sup>3</sup> / 200 ml/m<sup>3</sup>

Remark : SSC B

Version : 22.02.2021

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 100 ppm / 370 mg/m<sup>3</sup>

Peak limitation : 2(I)

Remark : Y

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : BILACRYL® PU D611  
Revision date : 02.10.2025  
Print date : 06.10.2025

Version (Revision) : 4.0.0 (3.0.0)

Version : 06.11.2015  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 150 ppm / 568 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 375 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000  
2,2',2''-NITRILOTRIETHANOL ; CAS No. : 102-71-6  
Limit value type (country of origin) : MAK ( CH )  
Parameter : E: inhalable fraction  
Limit value : 5 mg/m<sup>3</sup>  
Remark : SSC  
Version : 22.02.2021  
Limit value type (country of origin) : STEL ( CH )  
Parameter : E: inhalable fraction  
Limit value : 5 mg/m<sup>3</sup>  
Remark : SSC  
Version : 22.02.2021  
Limit value type (country of origin) : TRGS 900 ( D )  
Parameter : E: inhalable fraction  
Limit value : 1 mg/m<sup>3</sup>  
Peak limitation : 1(I)  
Remark : Y  
Version : 23.06.2022  
3-iodo-2-propynyl butylcarbamate ; CAS No. : 55406-53-6  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 0.005 ppm / 0.058 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Sh, Y  
Version : 23.06.2022  
REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) ; CAS No. : 55965-84-9  
Limit value type (country of origin) : MAK ( CH )  
Parameter : E: inhalable fraction  
Limit value : 0.2 mg/m<sup>3</sup>  
Remark : S SSC  
Version : 22.02.2021  
Limit value type (country of origin) : STEL ( CH )  
Parameter : E: inhalable fraction  
Limit value : 0.4 mg/m<sup>3</sup>  
Remark : S SSC  
Version : 22.02.2021

## 8.2 Exposure controls

### Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Personal protection equipment

#### Eye/face protection

Eye glasses with side protection

#### Skin protection

##### Hand protection

Tested protective gloves must be worn Use protective skin cream before handling the product.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : BILACRYL® PU D611  
Revision date : 02.10.2025  
Print date : 06.10.2025

Version (Revision) : 4.0.0 (3.0.0)

## Body protection

Wear anti-static footwear and clothing Following skin contact Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

## Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Safety characteristics

|                                           |              |                               |
|-------------------------------------------|--------------|-------------------------------|
| Initial boiling point and boiling range : | ( 1013 hPa ) | not applicable                |
| Flash point :                             |              | not applicable                |
| Vapour pressure :                         | ( 50 °C )    | not applicable                |
| Density :                                 | ( 20 °C )    | approx. 1.1 g/cm <sup>3</sup> |
| Solvent separation test :                 | ( 20 °C )    | < 3 %                         |
| Flow time :                               | ( 20 °C )    | approx. 100 s DIN-cup 4 mm    |

### 9.2 Other information

None

## 10. Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

No information available.

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.5 Incompatible materials

Oxidizing agent Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated.

### 10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## 11. Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Acute oral toxicity

|                  |                                                      |
|------------------|------------------------------------------------------|
| Parameter :      | LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )   |
| Exposure route : | Oral                                                 |
| Species :        | Rat                                                  |
| Effective dose : | 5660 mg/kg                                           |
| Parameter :      | LD50 ( 2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0 ) |
| Exposure route : | Oral                                                 |
| Species :        | Rat                                                  |
| Effective dose : | 2340 mg/kg                                           |
| Parameter :      | LD50 ( BRONOPOL (INN) ; CAS No. : 52-51-7 )          |
| Exposure route : | Oral                                                 |
| Species :        | Rat                                                  |

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** BILACRYL® PU D611  
**Revision date :** 02.10.2025  
**Print date :** 06.10.2025

**Version (Revision) :** 4.0.0 (3.0.0)

|                                  |                                                      |
|----------------------------------|------------------------------------------------------|
| Effective dose :                 | 254 mg/kg                                            |
| <b>Acute dermal toxicity</b>     |                                                      |
| Parameter :                      | LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )   |
| Exposure route :                 | Dermal                                               |
| Species :                        | Rabbit                                               |
| Effective dose :                 | 9999.99 mg/kg                                        |
| Parameter :                      | LD50 ( 2-DIMETHYLAMINOETHANOL ; CAS No. : 108-01-0 ) |
| Exposure route :                 | Dermal                                               |
| Species :                        | Rabbit                                               |
| Effective dose :                 | 1370 mg/kg                                           |
| Parameter :                      | LD50 ( BRONOPOL (INN) ; CAS No. : 52-51-7 )          |
| Exposure route :                 | Dermal                                               |
| Species :                        | Rat                                                  |
| Effective dose :                 | approx. 1600 mg/kg                                   |
| <b>Acute inhalation toxicity</b> |                                                      |
| Parameter :                      | LD50 ( BRONOPOL (INN) ; CAS No. : 52-51-7 )          |
| Exposure route :                 | Inhalation                                           |
| Species :                        | Rat                                                  |
| Effective dose :                 | > 588 mg/kg                                          |

### 11.2 Information on other hazards

#### Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Frequently or prolonged contact with skin may cause dermal irritation. The liquid splashed in the eyes may cause irritation and reversible damage. There no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

## 12. Ecological information

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Endocrine disrupting properties

No information available.

### 12.7 Other adverse effects

No information available.

### 12.8 Additional ecotoxicological information

No information available. Do not allow to enter into surface water or drains.

## 13. Disposal considerations

### 13.1 Waste treatment methods

**Directive 2008/98/EC (Waste Framework Directive)**

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : BILACRYL® PU D611  
Revision date : 02.10.2025  
Print date : 06.10.2025

Version (Revision) : 4.0.0 (3.0.0)

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

### 14. Transport information

#### 14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

#### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

#### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

#### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

#### 14.6 Special precautions for user

None

### 15. Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 75

##### National regulations

##### Technische Anleitung Luft (TA-Luft) ( D ) :

Weight fraction (Number 5.2.5. I) : < 5 %

##### Water hazard class

Classification according to AwSV - Class ( D ) : 1 (Slightly hazardous to water)

#### 15.2 Chemical Safety Assessment

No information available.

### 16. Other information

#### 16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Special rules for supplemental label elements for certain mixtures · 03. Hazardous ingredients · 07. Hints on joint storage - Storage class · 08. Occupational exposure limit values · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR) · 15. Restrictions on use · 15. Technische Anleitung zur Reinhaltung der Luft (TA-Luft) · 15. Water hazard class

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

#### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

#### 16.5 Relevant H- and EUH-phrases (Number and full text)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** BILACRYL® PU D611  
**Revision date :** 02.10.2025  
**Print date :** 06.10.2025

**Version (Revision) :** 4.0.0 (3.0.0)

---

|        |                                                                 |
|--------|-----------------------------------------------------------------|
| H226   | Flammable liquid and vapour.                                    |
| H301   | Toxic if swallowed.                                             |
| H302   | Harmful if swallowed.                                           |
| H304   | May be fatal if swallowed and enters airways.                   |
| H310   | Fatal in contact with skin.                                     |
| H312   | Harmful in contact with skin.                                   |
| H314   | Causes severe skin burns and eye damage.                        |
| H315   | Causes skin irritation.                                         |
| H317   | May cause an allergic skin reaction.                            |
| H318   | Causes serious eye damage.                                      |
| H319   | Causes serious eye irritation.                                  |
| H330   | Fatal if inhaled.                                               |
| H331   | Toxic if inhaled.                                               |
| H335   | May cause respiratory irritation.                               |
| H336   | May cause drowsiness or dizziness.                              |
| H351   | Suspected of causing cancer if inhaled.                         |
| H372   | Causes damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.                                     |
| H410   | Very toxic to aquatic life with long lasting effects.           |
| H411   | Toxic to aquatic life with long lasting effects.                |
| EUH071 | Corrosive to the respiratory tract.                             |

### 16.6 Training advice

None

### 16.7 Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---