according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

1. Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Thinner V102

Unique Formula Identifier: C440-20UN-G00E-NHX7

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Coatings and paints, fillers, putties, thinners. The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MONOPOL AG

Street/P.O.Box: Oberrohrdorferstrasse 51

Country code/Postal 5442 Fislisbach

code/Town/City:

 Telephone :
 +41 56 484 77 77

 Telefax :
 +41 56 484 77 99

 Contact :
 info@monopol-colors.ch

1.4 Emergency telephone number

+41 44 251 51 51

2. Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3; H226 - Flammable liquids: Category 3; Flammable liquid and vapour.

Acute Tox. 4; H312 - Acute toxicity (dermal): Category 4; Harmful in contact with skin.

Acute Tox. 4; H332 - Acute toxicity (inhalative) : Category 4; Harmful if inhaled.

Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

STOT SE 3; H335 - STOT-single exposure: Category 3; May cause respiratory irritation.

STOT RE 2; H373 - STOT-repeated exposure: Category 2; May cause damage to organs through prolonged or repeated

xposure.

Asp. Tox. 1; H304 - Aspiration hazard: Category 1; May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms







Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Dangei

Hazard components for labelling

MIXED XYLENE

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H312+H332 Harmful in contact with skin or if inhaled.

Page: 1/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P310 Immediately call a POISON CENTER/doctor/....

P331 Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to hazardous waste

Additional information

P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P302+P352 - IF ON SKIN: Wash with plenty of water/.... P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

3. Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

MIXED XYLENE; REACH No.: 01-2119488216-32-xxxx; EC No.: 905-588-0

Weight fraction : \geq 80 - < 85 %

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT RE 2; H373 Acute Tox. 4; H312

Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335

CYCLOHEXANONE; REACH No.: 01-2119453616-35; EC No.: 203-631-1; CAS No.: 108-94-1

Weight fraction : \geq 20 - < 25 %

Classification 1272/2008 [CLP]: Flam. Liq. 3; H226 Acute Tox. 4; H332

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

3.3 Additional information

mixture of solvents

4. First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. Keep at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

Remove contact lenses, keep eyelids open. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Page: 2/8

(EN / CH)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

Call a physician in any case! Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. See protective measures under point 7 and 8.

6.2 Environmental precautions

Cover drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

7. Handling and storage

7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. Take precautionary measures against static discharges. Wear anti-static footwear and clothing It is recommended to design all work processes always so that the following is excluded: Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Comply with the health and safety at work laws. For personal protection see Section 8. Respiratory protection necessary at: spray application

Protective measures

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Page: 3 / 8

(EN / CH)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

Always close containers tightly after the removal of product. Never use pressure to empty container. Only allow access to authorised staff. Keep away from sources of ignition - No smoking. Always close containers tightly after the removal of product. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Storage class (TRGS 510) (D): 3

Do not store together with

Do not store together with Acid alkali Oxidizing agent

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from sources of ignition - No smoking. Keep in a cool, well-ventilated place. Keep in a cool, well-ventilated place. Comply with the health and saftey at work laws.

7.3 Specific end use(s)

None

8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CYCLOHEXANONE; CAS No.: 108-94-1

Limit value type (country of origin): MAK (CH)

Limit value: 100 mg/m³ / 25 ml/m³

Remark: H SSC B Version: 22.02.2021 Limit value type (country of origin): STEL (CH)

Limit value: 200 mg/m³ / 50 ml/m³

Peak limitation: 1(I)
Remark: H,Y
Version: 06.11.2015
Limit value type (country of origin): STEL (EC)

Remark : H 08.06.2000 Limit value type (country of origin) : TWA (EC)

Limit value: 10 ppm / 40.8 mg/m³

Remark:

Version: 08.06.2000

8.2 Exposure controls

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Tested protective gloves must be worn Use protective skin cream before handling the product.

Body protection

Wear anti-static footwear and clothing Following skin contact Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

Page: 4/8

according to Regulation (EC) No. 1907/2006 (REACH)



°C

Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid
Colour: colourless
Odour: Like solvent.
Safety characteristics

Initial boiling point and boiling (1013 hPa) not applicable range:

Flash point : 23 **Vapour pressure :** (50 °C) not applicable

Density: (20 °C) 0.9 g/cm³

Solvent separation test: (20 °C) < 3 %

Flow time: (20 °C) 16 s DIN-cup 4 mm

9.2 Other information

None

10. Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

The product is chemically stable under recommended conditions of storage, use and temperature.

10.5 Incompatible materials

Oxidizing agent Exothermic reaction with: Alkali (lye), concentrated. Acid, concentrated.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute oral toxicity

Parameter: LD50 (CYCLOHEXANONE ; CAS No. : 108-94-1)

Exposure route: Oral
Species: Rat
Effective dose: 1620 mg/kg

Acute dermal toxicity

Parameter: LD50 (CYCLOHEXANONE ; CAS No. : 108-94-1)

Exposure route: Dermal
Species: Rabbit
Effective dose: 1000 mg/kg

Page: 5 / 8

(EN / CH)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

11.2 Information on other hazards

Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Frequently or prolonged contact with skin may cause dermal irritation. The liquid splashed in the eyes may cause irritation and reversible damage. There no data availble on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

12. Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

No information available. Do not allow to enter into surface water or drains.

13. Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

14. Transport information

14.1 UN number or ID number

UN 1915

14.2 UN proper shipping name

Land transport (ADR/RID)

Generated

Sea transport (IMDG)

Generated .

Air transport (ICAO-TI / IATA-DGR)

Generated

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 3
Classification code: F1

Page: 6 / 8





Trade name: Thinner V102

Revision date : 02.06.2025 Version (Revision): 4.0.0 (3.1.0)

Print date: 02.06.2025

Hazard identification number (Kemler

No.): **Tunnel restriction code:** D/E **Special Provisions:** LQ 5 | · E 1 3

Hazard label(s):

Sea transport (IMDG)

Class(es): 3 F-E / S-D EmS-No.: Special Provisions: LQ 5 | · E 1

Hazard label(s):

Air transport (ICAO-TI / IATA-DGR)

3 Class(es): **Special Provisions:** E 1 Hazard label(s):

14.4 Packing group

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

None

15. Regulatory information

$_{15.1}$ Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3

National regulations

Water hazard class

Classification according to AwSV - Class (D): 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

No information available.

16. Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) -Air transport (ICAO-TI / IATA-DGR) · 15. Water hazard class

16.2 Abbreviations and acronyms

16.3 Key literature references and sources for data

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Thinner V102

Revision date: 02.06.2025 **Version (Revision):** 4.0.0 (3.1.0)

Print date : 02.06.2025

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

16.6 Training advice

None

16.7 Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 8 / 8